

Midi Spike Spot

Technical specification / SPIKEM

Contents

Select a section or page number to jump to it. Use Contents in the footer to return.

01 Product overview	2
02 Light & electrical	3
03 Mechanical & construction	3
04 Service & circularity	3
05 Ordering	3

Generated from current saved product details, specification notes and published FAQs. Downloaded copies are dated snapshots. Regenerate after changes. Unanswered fields are omitted. Check suitability for your project before installation.

01 Product overview

Midi Spike Spot



Product code	SPIKEM
Product reference	9014
Rated power (standard LED)	6.6 W
Ingress protection	IP68
Standard cable length	2.00 m
Standard weight	570 g
Warranty period	10 years

Product record updated: 2026-09-19 00:56:29

Specification notes revision: 0

02 Light & electrical

Available LED options (colour / power)	3000K / 6.6W 2700K / 6.6W 2200K / 6.6W
--	--

03 Mechanical & construction

Body material by finish	Black powder coat: CNC machined 6082-T6 aluminium Green powder coat: CNC machined 6082-T6 aluminium Brass: CNC machined Brass CZ121 CorTen Powder coat: CNC machined 6082-T6 aluminium CUSTOM RAL: CNC machined 6082-T6 aluminium Terra brown (formerly Bronze (RAL 8040)): CNC machined 6082-T6 aluminium
Available finishes	Black powder coat; Green powder coat; Brass; CorTen Powder coat; CUSTOM RAL; Terra brown (formerly Bronze (RAL 8040))

04 Service & circularity

TM66 assessment score	2.6
-----------------------	-----

05 Ordering

Available options	Glare guard (Midi); 100mm longer rod; 200mm longer rod; 250mm longer rod; 300mm longer rod
-------------------	--